

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 April 2004 (22.04.2004)


PCT

(10) International Publication Number
WO 2004/032736 A1

- (51) International Patent Classification⁷: **A61B 5/00**
- (21) International Application Number:
PCT/IB2003/004152
- (22) International Filing Date:
18 September 2003 (18.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
02079214.9 11 October 2002 (11.10.2002) EP
- (71) Applicant (for all designated States except DE, US):
KONINKLIJKE PHILIPS ELECTRONICS N.V.
[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven
(NL).
- (72) Inventors; and
(75) Inventors/Applicants (for US only): **SUCH, Olaf**
[DE/DE]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven
(NL). **VOGTMEIER, Gereon** [DE/DE]; c/o Prof. Hol-
stlaan 6, NL-5656 AA Eindhoven (NL). **LAUTER, Josef**
[DE/DE]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven
(NL). **REITER, Harald** [DE/DE]; c/o Prof. Holstlaan
6, NL-5656 AA Eindhoven (NL). **REICHINGER,**
Christian [DE/DE]; c/o Prof. Holstlaan 6, NL-5656 AA
Eindhoven (NL). **SCHMIDT, Ralf** [DE/DE]; c/o Prof.
Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agent: **SCHOUTEN, Marcus, M.**; Philips Intellectual
Property & Standards, Prof. Holstlaan 6, NL-5656 AA
Eindhoven (NL).

[Continued on next page]

(54) Title: **POWER SAVING UPLINK FOR BIOSENSORS**



(57) Abstract: A system for monitoring a physiological condition of an individual. The system (1) comprises sensing means (3) arranged to pick up a first signal (M) in a first mode of the system, said first signal being representative of the physiological condition and to forward the first signal to a signal processing unit (33). The system comprises an actuatable control unit (2) positioned remote from the signal processing unit, the control unit (2) being suitable to generate a second signal (T) arranged to be superimposed on the first signal (M). The signal processing unit (33, 37) is arranged to decode the second signal and to make the system enter into a second mode upon receipt of the second signal (T).